



型号 Type	尺寸 Dimension(mm)						凸缘号 孔数 Number of poles on the flange
	P	M	N	S	T	L	
71	120	100	80	10	3	310	4
	160	130	110				
	140	100	80				
	200	165	130	12	3.5	298	
80	120	100	80	10	3	369	
	160	130	110				
	200	165	12	12	3.5		

型号 Type	尺寸 Dimension(mm)						凸缘号 孔数 Number of poles on the flange
	P	M	N	S	T	L	
80	140	100	80	10	3	355	4
	250	215	180	15	4	337	
	300	265	230				
90S	120	100	80	10	3	388	
	160	130	110				
	200	165	130	12	3.5		
	140	100	80	10	3	385	

技术数据 Technical data

型号 Type	尺寸 Dimension(mm)						凸缘号 孔数 Number of poles on the flange
	P	M	N	S	T	L	
90S	250	215	180	15	4	364	
	300	265	230				
	120	100	80				

型号 Type	尺寸 Dimension(mm)						凸缘号 孔数 Number of poles on the flange
	P	M	N	S	T	L	
90S	250	215	180	15	4	364	
	300	265	230				
	120	100	80				

90L	160	130	110	10	3	432		
	200	165	130	12	3.5			
	140	100	80	10	3	429		
	250	215	180	15	4	408		
	300	265	230					
100	120	100	80	10	3	427		
	140	100	80			445		
	160	130	110			12	3.5	437
	200	165	130					
	250	215	180	15	4			402
	300	265	230					
	350	300	250	19	5	405		
112	160	130	110	10	3	483		
	200	165	130	12	3.5			
	250	215	180	15	4		434	
	300	265	230					
	350	300	250	19	5			
132S	160	130	110	10	3	523		
	200	165	130	12	3.5			
	250	215	180	15	4		484	
	300	265	230					
	350	300	250	19	5	434		
	400	350	300					
	450	400	350					

90L	160	130	110	10	3	432		
	200	165	130	12	3.5			
	140	100	80	10	3	429		
	250	215	180	15	4	408		
	300	265	230					
100	120	100	80	10	3	427		
	140	100	80			445		
	160	130	110			12	3.5	437
	200	165	130					
	250	215	180	15	4			402
	300	265	230					
	350	300	250	19	5	405		
112	160	130	110	10	3	483		
	200	165	130	12	3.5			
	250	215	180	15	4		434	
	300	265	230					
	350	300	250	19	5			
132S	160	130	110	10	3	523		
	200	165	130	12	3.5			
	250	215	180	15	4		484	
	300	265	230					
	350	300	250	19	5	434		
	400	350	300					
	450	400	350					

132M	160	130	110	10	3	567
	200	165	130	12	3.5	
	250	215	180	15	4	
	300	265	230			
	350	300	250	19	5	528
	400	350	300			530
	450	400	350			
160M	200	165	130	12	3.5	636
	250	215	180	15	4	

132M	160	130	110	10	3	567
	200	165	130	12	3.5	
	250	215	180	15	4	
	300	265	230			
	350	300	250	19	5	528
	400	350	300			530
	450	400	350			
160M	200	165	130	12	3.5	636
	250	215	180	15	4	