

技术数据 Technical data

型号 Type 极数		功率 Output (kw)	同步转速 Speed (r/min)	电流 Current (A)	电压 Voltage (A)	效率 Efficiency (%)	功率因数 Power Factory (COS Φ)	堵转转矩		堵转电流		噪声 Noise Lw dB(a)
								额定转矩 Locked Rotor Torque	额定电流 Locked Rotor Current	噪声 Noise Lw dB(a)		
								Rated Torque	Rated Current			
YDT80S-2/4	2	0.55	3000	1.44	380	68	0.85	2	6.5	79		
	4	0.45	1500	1.54	380	58	0.74	1.4	5.5			
YDT80M-2/4	2	0.75	3000	2.5	380	70	0.85	2	6.5	79		
	4	0.55	1500	1.75	380	54	0.74	1.4	5.5			
YDT90L-2/4	2	1.5	3000	3.41	380	71	0.85	2	6.5	83		
	4	0.5	1500	1.73	380	70	0.77	1.4	5.5			
YDT100L1-2/4	2	2.50	3000	5.39	380	82	0.86	2	6.5	87		
	4	0.65	1500	1.65	380	74	0.81	1.4	5.5			
YDT100L2--2/4	2	3.10	3000	6.45	380	82	0.89	2	6.5	87		
	4	0.80	1500	1.93	380	76	0.83	1.4	5.5			
YDT112M-2/4	2	4	3000	8.1	380	82	0.89	2	6.5	87		
	4	1.2	1500	3.5	380	80	0.83	1.4	5.5			
YDT132S-2/4	2	5.5	3000	11.6	380	83	0.89	1.9	6.5	91		
	4	1.1	1500	2.9	380	80	0.84	1.3	5.5			
YDT132M-2/4	2	7.5	3000	15.4	380	85	0.89	1.9	6.5	91		
	4	1.5	1500	3.5	380	83	0.85	1.3	5.5			
YDT160M-2/4	2	12.5	3000	25.2	380	86	0.89	1.9	6.5	95		
	4	2.80	1500	7.2	380	85	0.85	1.3	5.5			
YDT160L-2/4	2	16.0	3000	31.4	380	87	0.89	1.9	6.5	95		
	4	3.80	1500	8.1	380	85	0.85	1.3	5.5			
YDT90S-4/6	4	0.85	3000	2.32	380	70	0.79	1.9	6.5	75		
	6	0.3	1500	0.92	380	63	0.68	1.3	5.5			
YDT90L-4/6	4	1.1	1500	3.1	380	72	0.79	1.8	7	75		
	6	0.3	1000	0.92	380	68	0.7	0.6	6			
YDT100L1-4/6	4	2.2	1500	5.22	380	80	0.8	1.8	7	78		
	6	0.70	1000	2.80	380	73	0.7	0.6	6			
YDT100L2-4/6	4	2.5	1500	5.86	380	81	0.8	1.8	7	78		
	6	0.90	1000	2.64	380	74	0.7	0.6	6			

YDT112M-4/6	4	3	1500	6.83	380	82	0.82	1.8	7	82
	6	1.2	1000	3.21	380	78	0.75	0.6	6	
YDT132S-4/6	4	4	1500	8.29	380	84	0.82	1.8	7	82
	6	1.3	1000	3.31	380	81	0.75	0.6	6	
YDT132M-4/6	4	6	1500	12.18	380	85	0.85	1.8	7	82
	6	2	1000	4.83	380	83	0.86	0.6	6	

技术数据 Technical data

型号 Type	极数 NO of poles	功率 Output (kw)	同步转速 Speed (r/min)	电流 Current (A)	电压 Voltage (V)	效率 Efficiency (%)	功率因数 Power Factor (COS Φ)	堵转转矩		堵转电流		噪声 Noise L _w dB(a)
								额定转矩	额定电流	Locked Rotor Torque	Locked Rotor Current	
								Rated Torque	Rated Current			
YDT160L-4/6	4	11	1500	22.98	380	88	0.85	1.8	7.5	86		
	6	5	1000	12.6	380	83	0.78	1.6	5			
YDT180M-4/6	4	13	1500	30.8	380	87	0.85	1.5	7.5	90		
	6	4.5	1000	10.7	380	81	0.76	1.5	5			
YDT180L-4/6	4	17	1500	35.8	380	87	0.85	1.5	7.5	90		
	6	5.5	1000	15.6	380	81	0.78	1.5	5			
YDT200L-4/6	4	24	1500	49.2	380	88	0.86	1.5	7.5	90		
	6	8.0	1000	18.5	380	83	0.78	1.5	5			
YDT225S-4/6	4	3.3	1500	66.7	380	89	0.87	1.5	7.5	92		
	6	11.0	1000	24.5	380	84	0.86	1.5	5			
YDT225M-4/6	4	38	1500	77.1	380	90	0.87	1.5	7.5	92		
	6	17	1000	34.6	380	85	0.86	1.5	5			
YDT250M-4/6	4	47	1500	86.13	380	90	0.87	1.5	7.5	94		
	6	16.0	1000	31.17	380	85	0.86	1.5	5			
YDT280S-4/6	4	55	1500	104.21	380	90	0.891	1.5	7.5	94		
	6	18.5	1000	38.19	380	85	0.866	1.5	5			
YDT280M1-4/6	4	70	1500	131.17	380	91	0.891	1.5	7.5	98		
	6	25.0	1000	50.42	380	87	0.866	1.5	5			
YDT280M2-4/6	4	84	1500	157.41	380	91	0.891	1.5	7.5	98		
	6	28.0	1000	56.47	380	87	0.866	1.5	5			
YDT315S-4/6	4	95	1500	179.88	380	91	0.907	1.5	7.5	100		
	6	32.0	1000	62.94	380	89	0.868	1.5	5			
YDT315M-4/6	4	115	1500	215.4	380	92	0.907	1.5	7.5	100		
	6	38.0	1000	73.91	380	90	0.868	1.5	5			
YDT315L-4/6	4	135	1500	245.81	380	92	0.907	1.5	7.5	100		

YDT315L1-4/0	6	45.0	1000	87.52	380	90	0.868	1.5	5	100
YDT315L2-4/6	4	160	1500	288.2	380	93	0.907	1.5	7.5	100
	6	55.0	1000	105.8	380	91	0.868	1.5	5	
YDT90S-4/8	4	1	1500	2.49	380	70	0.87	1.9	7.5	75
	8	0.22	750	0.96	380	55	0.63	1.5	5	
YDT90L-4/8	4	1.3	1500	3.15	380	72	0.87	1.9	7.5	75
	8	0.30	750	12.5	380	58	0.63	1.5	5	
YDT100L-4/8	4	1.5	1500	3.28	380	80	0.88	1.9	7.5	78
	8	0.55	750	2.04	380	65	0.63	1.5	5	
YDT112M-4/8	4	3.2	1500	7.04	380	83	0.88	1.9	7.5	82
	8	0.90	750	3.06	380	71	0.63	1.5	5	
YDT132S-4/8	4	4.5	1500	9.25	380	84	0.88	2	7.5	82
	8	1.10	750	3.48	380	75	0.64	1.2	5	
YDT132M-4/8	4	6.3	1500	12.65	380	85	0.89	2	7.5	82
	8	1.5	750	4.5	380	78	0.65	1.2	5	
YDT160L-4/8	4	11	1500	21.8	380	86	0.89	2	7.5	86
	8	3.0	750	9.3	380	83	0.66	1.2	5	
YDT180M-4/8	4	16	1500	31.04	380	88	0.89	2	7.5	90
	8	4.00	750	11.05	380	84	0.72	1.2	5	
YDT180L-4/8	4	19.5	1500	37.4	380	89	0.89	2	7.5	90
	8	5.00	750	13.8	380	85	0.72	1.2	5	
YDT200L-4/8	4	29	1500	55.32	380	90	0.89	2	7.5	90
	8	7.50	750	17.7	380	87	0.74	1.2	5	
YDT225M-4/8	4	34	1500	64.68	380	91	0.89	2	7.5	92
	8	10	750	26.51	380	88	0.74	1.3	5	
YDT250M-4/8	4	52	1500	96.47	380	91	0.9	2	7.5	94
	8	14.5	750	31.29	380	88	0.8	1.3	5	
YDT280S-4/8	4	65	1500	117.96	380	91	0.92	2	7.5	98
	8	17.0	750	35.39	380	89	0.82	1.3	5	
YDT280M4-4/8	4	75	1500	136.11	380	91	0.92	2	7.5	98
	8	18.5	750	38.09	380	90	0.82	1.3	5	
YDT315S-4/8	4	92	1500	165.17	380	91	0.93	2	7.5	100
	8	25.0	750	51.47	380	90	0.82	1.3	5	

技术数据 Technical data

型号 Type	极数 NO of poles	功率 Output (kw)	同步转速 Speed (r/MIN)	电流 Current (A)	电压 Voltage (V)	效率 Efficiency (%)	功率因数 Power Factor (COSφ)	堵转转矩	堵转电流	噪声 Noise Lw dB(a)
								额定转矩 Locked Rotor Torque Rated Torque	额定电流 Locked Rotor Current Rated Current	

	Speed (rpm)	(kW)	(HP)	(%)	(%)	(%)	(%)	(%)	Rated Torque	Rated Current	(%)
YDT315M-4/8	4	110	1500	159.34	380	92	0.93	2	7.5	100	
	8	30.0	750	61.08	380	91	0.82	1.3	5		
YDT315M-4/8	4	135	1500	239.74	380	92	0.93	2	7.5	100	
	8	36.0	750	73.3	380	91	0.82	1.3	5		
YDT315L2-4/8	4	155	1500	275.25	380	92	0.93	2	7.5	100	
	8	41.0	750	83.48	380	91	0.82	1.3	5		
YDT90L-6/8	6	0.65	1500	1.84	380	67	0.72	1.8	7	73	
	8	0.45	750	1.94	380	56	0.6	1.6	6		
YDT90L2-6/8	6	0.75	1500	2.07	380	67	0.72	1.8	7	73	
	8	0.45	750	1.9	380	56	0.6	1.6	6		
YDT100L-6/8	6	1.3	1500	3.81	380	71	0.73	1.8	7	73	
	8	0.55	750	2.25	380	62	0.6	1.6	6		
YD1T00L2-6/8	6	1.6	1500	4.5	380	74	0.73	1.8	7	73	
	8	0.75	750	2.88	380	66	0.6	1.6	6		
YDT112M-6/8	6	2	1500	5.63	380	74	0.73	1.8	7	75	
	8	0.85	750	3.16	380	66	0.61	1.6	6		
YDT132S-6/8	6	2.4	1500	4.9	380	79	0.73	1.8	7	79	
	8	1.1	750	2.9	380	73	0.62	1.6	6		
YDT132M-6/8	6	3.7	1500	7.8	380	80	0.73	1.8	7	79	
	8	1.8	750	4.7	380	76	0.62	1.6	6		
YDT160M-6/8	6	6	1500	13.6	380	84	0.73	1.8	7	83	
	8	2.6	750	7.1	380	80	0.62	1.6	6		
YDT160L-6/8	6	8	1500	16.8	380	86	0.73	1.8	7	83	
	8	3.7	750	9.7	380	82	0.62	1.6	6		
YDT180L-6/8	6	12	1500	6.1	380	86	0.73	1.5	7	86	
	8	5.5	750	15.2	380	84	0.62	1.5	6		
YDT200L1-6/8	6	17	1500	34.74	380	87	0.76	1.5	7	88	
	8	8.0	750	20.02	380	82	0.65	1.5	6		
YDT200L2-6/8	6	20	1500	42.78	380	88	0.76	1.5	7	88	
	8	10	750	25.65	380	83	0.65	1.5	6		
YDT225M-6/8	6	25	1500	50.93	380	89	0.78	1.5	7	92	
	8	12	750	31.2	380	87	0.67	1.5	6		
YDT250M1-6/8	6	30	1500	56.9	380	90	0.78	1.5	7	92	
	8	18	750	38.8	380	87	0.67	1.5	6		
YDT250M2-6/8	6	37	1500	69.8	380	90	0.78	1.5	7	92	
	8	22.0	750	49.7	380	87	0.67	1.5	6		
YDT280M1-6/8	6	45.0	1500	84	380	90	0.8	1.5	7	96	
	8	22	750	53	380	88	0.68	1.5	6		
YDT280M1-6/8	6	55	1500	110.79	380	91	0.8	1.5	7	96	
	8	28.0	750	70.3	380	89	0.68	1.5	6		
	6	65	1500	127.98	380	91	0.81	1.5	7	--	

YDT280M3-6/8	8	32.0	750	80.34	380	89	0.68	1.5	6	96
	6	75	1500	145.71	380	91	0.82	1.5	7	
YDT315S-6/8	8	37.0	750	90.53	380	90	0.69	1.5	6	100
	6	90	1500	173.26	380	92	0.82	1.5	7	
YDT315M-6/8	8	45.0	750	108.89	380	91	0.69	1.5	6	100
	6	110	1500	214.27	380	92	0.84	1.5	7	
YDT315L1-6/8	8	55.0	750	131.19	380	91	0.7	1.5	6	100
	6	132	1500	259.52	380	92	0.84	1.5	7	
YDT315L2-6/8	8	66.0	750	157.42	380	91	0.7	1.5	6	100
	6	22	1500	44.5	380	90	0.83	1.5	6.5	
YDT225M-6/12	12	4.4	500	15.7	380	75	0.65	1.5	5	92
	6	30	1500	58.8	380	91	0.84	1.5	6.5	
YDT250M-6/12	12	6	500	17.2	380	80	0.7	1.3	5	92
	6	37	1500	72.2	380	92	0.85	1.5	6.5	
YDT280S-6/12	12	7.5	500	21.5	380	80	0.75	1.3	5	94
	6	45	1500	84.6	380	92	0.85	1.5	6.5	
YDT280M-6/12	12	9	500	23.6	380	82	0.75	1.3	5	94
	6	45	1500	84.6	380	92	0.85	1.5	6.5	