

技术数据 Technical data

额定电压 Rated Voltage 380V		额定频率 Rated Frequency 50Hz		电压 Voltage 22~ 380V		频率 Frequency 5~50Hz		
型号 Type	额定功率 Rated Output (kw)	额定电流 Rated Current (A)	额定转矩 Rated Torque (rpm)	转速 Speed (r/min)	效率 Efficiency (%)	功率因数 Power Factory (COS ϕ)	噪声 Noise Lw dB(a)	重量 Weight (Kw)
801-4	0.55	1.5	3.5	139~1390	73.0	0.76	60	17.5
802-4	0.75	2	4.8	139~1390	74.5	0.76	60	18.5
90S-4	1.1	2.7	7	140~1400	78.0	0.78	63	24
90L-4	1.5	3.7	9.5	140~1400	79.0	0.79	63	28
100L1-4	2.2	5.2	14	142~1420	81.0	0.82	65	36
100L2-4	3	6.9	19.1	142~1420	82.5	0.81	65	40
112M-4	4	8.9	25.5	144~1440	84.5	0.82	70	47
132S-4	5.5	11.6	35	144~1440	85.5	0.84	74	63
132M-4	7.5	15.4	47.7	144~1440	87.0	0.85	74	76
160M-4	11	22.6	70	146~1460	88.0	0.84	78	118
160L-4	15	30.3	95.5	146~1460	88.5	0.86	78	136
180M-4	18.5	35.9	117.8	147~1470	91.0	0.86	78	170
180L-4	22	42.5	140.1	147~1470	91.5	0.86	78	192
200L-4	30	56.7	191	147~1470	92.2	0.87	80	250
800-6	0.18	0.75	1.7	91~910	59.0	0.63	53	16
801-6	0.25	0.95	2.4	91~910	63.0	0.64	58	16

技术数据 Technical data

额定电压 Rated Voltage 380V		额定频率 Rated Frequency 50Hz		电压 Voltage 22~ 380V		频率 Frequency 5~50Hz		
型号 Type	额定功率 Rated Output (kw)	额定电流 Rated Current	额定转矩 Rated Torque	转速 Speed	效率 Efficiency (%)	功率因数 Power Factor (COS ϕ)	噪声 Noise Lw dB(a)	重量 Weight (Kw)
802-6	0.37	1.2	3.5	91~910	68.0	0.64	58	17
803-6	0.55	1.7	5.3	91~910	71	0.65	58	18
90S-6	0.75	2.3	7.2	91~910	72.5	0.70	61	26
90L-6	1.1	3.2	10.5	91~910	73.5	0.72	61	28
100L1-6	1.5	4	14.3	94~940	77.5	0.74	63	34
112M-6	2.2	5.8	21	94~940	80.5	0.74	63	41
132S1-6	3	7.2	28.6	96~960	83.0	0.76	67	61
132S2-6	4	9.4	38.2	96~960	84.0	0.77	67	66
132M-6	5.5	12.5	52.5	96~960	85.3	0.78	67	80
160M-6	7.5	17	71.6	97~970	86.0	0.78	71	115
160L-6	11	24.6	105	97~970	87.0	0.78	71	136
180L-6	15	31.4	143.2	97~970	89.5	0.81	74	182
200L1-6	18.5	37.6	176.7	97~970	89.8	0.83	74	230
200L2-6	22	44.5	210.1	97~970	90.2	0.83	74	255
801-8	0.18	1.1	2.3	70~700	58.0	0.55	50	16
802-8	0.25	1.25	3.2	70~700	62.0	0.56	55	16
803-8	0.37	1.5	4.7	70~700	65.0	0.58	55	18
90S1-8	0.37	1.5	4.7	70~700	65.0	0.58	55	25
90S2-8	0.55	1.9	7	70~700	67.0	0.60	58	26

90L-8	0.75	2.7	9.5	70~700	71.0	0.60	58	28
100L1-8	0.75	2.7	9.5	70~700	71.0	0.60	58	34
100L2-8	1.1	3.5	14	70~700	73.0	0.65	58	35
112M-8	1.5	4.5	19.1	70~700	75.0	0.67	60	41
132S1-8	2.2	5.8	28	71~710	80.5	0.71	62	61
132S2-8	3	7.7	38.1	71~710	82.0	0.72	62	72
160MI-8	41	9.9	50.9	72~720	84.0	0.73	65	100
160M2-8	5.5	13.3	70	72~720	85.0	0.74	65	112
160L-8	7.5	17.7	95.5	72~720	86.0	0.75	68	136
180L-8	11	25.1	140.1	73~730	87.5	0.77	68	182
200L-8	15	34	191	73~730	88	0.76	71	280

注：

若有特殊要求，可按客户需要提供。

Please contact us with your requirement.